



SAFETY DATA SHEET

Issue Date 12-Jan-2018

Revision Date 07-Sep-2021

Version H

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

Product identifier

Product Name Niobium Alloy Powder (flammable)

Other means of identification

Product Code SAC047

UN/ID No. 3089

Synonyms All niobium alloy powders, columbium alloy powders, C103 powder (former product #516)

Recommended use of the chemical and restrictions on use

Recommended Use Alloy product manufacture.

Uses advised against

Details of the supplier of the safety data sheet

Manufacturer Address

ATI, 1000 Six PPG Place, Pittsburgh, PA
15222 USA

Emergency telephone number

Emergency Telephone Chemtrec: 1-800-424-9300

2. HAZARDS IDENTIFICATION

Classification

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Flammable solids

Category 1

Label elements

Emergency Overview

Danger

Hazard statements

Flammable solids



Appearance Powder

Physical state Solid

Odor Odorless

Precautionary Statements - Prevention

Wear protective gloves/protective clothing/eye protection

Keep away from heat/sparks/open flames/hot surfaces. - No smoking

Ground/bond container and receiving equipment

If dust clouds can occur, use explosion-proof electrical/ ventilating/lighting/equipment

Precautionary Statements - Response

In case of fire: Use salt (NaCl) for extinction.

Hazards not otherwise classified (HNOC)

Not applicable

Other Information

When product is subjected to welding, burning, melting, sawing, brazing, grinding, buffing, polishing, or other similar heat-generating processes, the following potentially hazardous airborne particles and/or fumes may be generated:

Titanium dioxide an IARC Group 2B carcinogen.

Vanadium pentoxide (V₂O₅) affects eyes, skin, respiratory system.

Soluble molybdenum compounds such as molybdenum trioxide may cause lung irritation.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Synonyms All niobium alloy powders, columbium alloy powders, C103 powder (former product #516).

Chemical Name	CAS No.	Weight-%
Niobium (Columbium)	7440-03-1	40 - >99
Titanium	7440-32-6	0 - 60
Aluminum	7429-90-5	0 - 50
Tantalum	7440-25-7	0 - 30
Tungsten	7440-33-7	0 - 30
Hafnium	7440-58-6	0 - 30
Vanadium	7440-62-2	0 - 10
Molybdenum	7439-98-7	0 - 10
Zirconium	7440-67-7	0 - 5
Hydrogen	1333-74-0	0 - 1.2

4. FIRST AID MEASURES

First aid measures

Eye contact In the case of particles coming in contact with eyes during processing, treat as with any foreign object.

Skin Contact None under normal use conditions.

Inhalation If excessive amounts of smoke, fume, or particulate are inhaled during processing, remove to fresh air and consult a qualified health professional.

Ingestion IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell.

Most important symptoms and effects, both acute and delayed

Symptoms None anticipated.

Indication of any immediate medical attention and special treatment needed

Note to physicians Treat symptomatically.

5. FIRE-FIGHTING MEASURES

Suitable extinguishing media

Isolate large fires and allow to burn out. Smother small fires with salt (NaCl).

Unsuitable extinguishing media Do not spray water on burning metal as an explosion may occur. This explosive characteristic is caused by the hydrogen and steam generated by the reaction of water with

the burning material.

Specific hazards arising from the chemical

Intense heat. Very fine, high surface area material resulting from processing this product may ignite spontaneously at room temperature. WARNING: Fine particles of this product may form combustible dust-air mixtures. Keep particles away from all ignition sources including heat, sparks, and flame. Prevent dust accumulations to minimize combustible dust hazard.

Hazardous combustion products Titanium dioxide an IARC Group 2B carcinogen. Vanadium pentoxide (V2O5) affects eyes, skin, respiratory system. Soluble molybdenum compounds such as molybdenum trioxide may cause lung irritation.

Explosion data

Sensitivity to Mechanical Impact None.

Sensitivity to Static Discharge May be ignited by heat, sparks or flames.

Protective equipment and precautions for firefighters

Firefighters should wear self-contained breathing apparatus and full firefighting turnout gear.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal precautions Use personal protective equipment as required.

For emergency responders Use personal protective equipment as required. Follow Emergency Response Guidebook, Guide No. 170.

Environmental precautions

Environmental precautions Collect spillage to prevent release to the environment.

Methods and material for containment and cleaning up

Methods for containment Prevent further leakage or spillage if safe to do so.

Methods for cleaning up Sweep or shovel material into dry containers using non-sparking tools. Avoid creating uncontrolled dust.

7. HANDLING AND STORAGE

Precautions for safe handling

Advice on safe handling Very fine, high surface area material resulting from grinding, buffing, polishing, or similar processes of this product may ignite spontaneously at room temperature. WARNING: Fine particles of this product may form combustible dust-air mixtures. Keep particles away from all ignition sources including heat, sparks, and flame. Prevent dust accumulations to minimize combustible dust hazard.

Conditions for safe storage, including any incompatibilities

Storage Conditions Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity). For long-term storage, keep sealed in argon-filled steel drums.

Incompatible materials Dissolves in hydrofluoric acid. Ignites in the presence of fluorine. When heated above 200°C, reacts exothermically with the following: Chlorine, bromine, halocarbons, carbon tetrachloride, carbon tetrafluoride, and freon.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Chemical Name	ACGIH TLV	OSHA PEL
---------------	-----------	----------

Niobium (Columbium) 7440-03-1	-	-
Titanium 7440-32-6	-	-
Aluminum 7429-90-5	TWA: 1 mg/m ³ respirable fraction	TWA: 15 mg/m ³ total dust TWA: 5 mg/m ³ respirable fraction
Tungsten 7440-33-7	STEL: 10 mg/m ³ STEL: 10 mg/m ³ W TWA: 5 mg/m ³ TWA: 5 mg/m ³ W	(vacated) STEL: 10 mg/m ³ (vacated) STEL: 10 mg/m ³ W
Tantalum 7440-25-7	-	TWA: 5 mg/m ³
Hafnium 7440-58-6	TWA: 0.5 mg/m ³ TWA: 0.5 mg/m ³ Hf	TWA: 0.5 mg/m ³
Vanadium 7440-62-2	-	Ceiling: 0.5 mg/m ³ V2O5 respirable dust Ceiling: 0.1 mg/m ³ V2O5 fume
Molybdenum 7439-98-7	TWA: 10 mg/m ³ inhalable fraction TWA: 3 mg/m ³ respirable fraction	-
Zirconium 7440-67-7	STEL: 10 mg/m ³ STEL: 10 mg/m ³ Zr TWA: 5 mg/m ³ TWA: 5 mg/m ³ Zr	TWA: 5 mg/m ³ Zr (vacated) STEL: 10 mg/m ³ (vacated) STEL: 10 mg/m ³ Zr
Hydrogen 1333-74-0	-	-

Appropriate engineering controls

Engineering Controls Avoid generation of uncontrolled particles.

Individual protection measures, such as personal protective equipment

Eye/face protection When airborne particles may be present, appropriate eye protection is recommended. For example, tight-fitting goggles, foam-lined safety glasses or other protective equipment that shield the eyes from particles.

Skin and body protection Fire/flame resistant/retardant clothing may be appropriate during hot work with the product.

Respiratory protection When particulates/fumes/gases are generated and if exposure limits are exceeded or irritation is experienced, proper approved respiratory protection should be worn. Positive-pressure supplied air respirators may be required for high airborne contaminant concentrations. Respiratory protection must be provided in accordance with current local regulations.

General Hygiene Considerations Handle in accordance with good industrial hygiene and safety practice.

9. PHYSICAL AND CHEMICAL PROPERTIES**Information on basic physical and chemical properties**

Physical state	Solid	Odor	Odorless
Appearance	Powder	Odor threshold	Not applicable
Color	Metallic gray or silver		
Property	Values	Remarks • Method	
pH	-	Not applicable	
Melting point / freezing point	2470 °C / 4480 °F		
Boiling point / boiling range	-		
Flash point	-		
Evaporation rate	-	Not applicable	
Flammability (solid, gas)	-	Flammable	
Flammability Limit in Air			
Upper flammability limit:	-		
Lower flammability limit:	-		
Vapor pressure	-	Not applicable	
Vapor density	-	Not applicable	
Specific Gravity	8.57		
Water solubility	Insoluble		

Solubility in other solvents	-	
Partition coefficient	-	Not applicable
Autoignition temperature	-	Not applicable
Decomposition temperature	-	Not applicable
Kinematic viscosity	-	Not applicable
Dynamic viscosity	-	Not applicable
Explosive properties	Not applicable	
Oxidizing properties	Not applicable	

Other Information

Softening point	-
Molecular weight	-
VOC Content (%)	Not applicable
Density	-
Bulk density	260 lb/ft3

10. STABILITY AND REACTIVITY**Reactivity**

Not applicable

Chemical stability

Stable under normal conditions.

Possibility of Hazardous Reactions

None under normal processing.

Hazardous polymerization

Hazardous polymerization does not occur.

Conditions to avoid

Dust formation and dust accumulation.

Incompatible materials

Dissolves in hydrofluoric acid. Ignites in the presence of fluorine. When heated above 200°C, reacts exothermically with the following: Chlorine, bromine, halocarbons, carbon tetrachloride, carbon tetrafluoride, and freon.

Hazardous Decomposition Products

When product is subjected to welding, burning, melting, sawing, brazing, grinding, buffing, polishing, or other similar heat-generating processes, the following potentially hazardous airborne particles and/or fumes may be generated: Titanium dioxide an IARC Group 2B carcinogen. Vanadium pentoxide (V2O5) affects eyes, skin, respiratory system. Soluble molybdenum compounds such as molybdenum trioxide may cause lung irritation.

11. TOXICOLOGICAL INFORMATION**Information on likely routes of exposure****Product Information**

Inhalation	Product not classified.
Eye contact	Product not classified.
Skin Contact	Product not classified.
Ingestion	Product not classified.

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
Niobium (Columbium) 7440-03-1	> 10,000 mg/kg bw	> 2000 mg/kg bw	-
Titanium	> 5000 mg/kg bw	-	-

7440-32-6			
Aluminum 7429-90-5	15,900 mg/kg bw	-	> 1 mg/L
Tungsten 7440-33-7	> 2000 mg/kg bw	> 2000 mg/kg bw	> 5.4 mg/L
Tantalum 7440-25-7	> 2000 mg/kg bw	> 2000 mg/kg bw	> 5.18 mg/L
Hafnium 7440-58-6	> 5000 mg/kg bw	-	>4.3mg/L
Vanadium 7440-62-2	> 2000 mg/kg bw	-	-
Molybdenum 7439-98-7	> 2000 mg/kg bw	> 2000 mg/kg bw	> 5.10 mg/L
Zirconium 7440-67-7	> 5000 mg/kg bw	-	>4.3 mg/L
Hydrogen 1333-74-0	-	-	> 15000 ppm (Rat) 1 h

Information on toxicological effects

Symptoms None known.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Acute toxicity Product not classified.
Skin corrosion/irritation Product not classified.
Serious eye damage/eye irritation Product not classified.
Sensitization Product not classified.
Germ cell mutagenicity Product not classified.
Carcinogenicity Product not classified.

Reproductive toxicity Product not classified.
STOT - single exposure Product not classified.
STOT - repeated exposure Product not classified.
Aspiration hazard Product not classified.

12. ECOLOGICAL INFORMATION

Ecotoxicity

This product as shipped is not classified for aquatic toxicity.

Chemical Name	Algae/aquatic plants	Fish	Toxicity to microorganisms	Crustacea
Niobium (Columbium) 7440-03-1	-	-	-	-
Titanium 7440-32-6	The 72 h EC50 of titanium dioxide to <i>Pseudokirchnerella subcapitata</i> was 61 mg of TiO ₂ /L.	The 96 h LC50 of titanium dioxide to <i>Cyprinodon variegatus</i> was greater than 10,000 mg of TiO ₂ /L. The 96 h LC50 of titanium dioxide to <i>Pimephales promelas</i> was greater than 1,000 mg of TiO ₂ /L.	The 3 h EC50 of titanium dioxide for activated sludge were greater than 1000 mg/L.	The 48 h EC50 of titanium dioxide to <i>Daphnia Magna</i> was greater than 1000 mg of TiO ₂ /L.
Aluminum 7429-90-5	The 96-h EC50 values for reduction of biomass of <i>Pseudokirchneriella subcapitata</i> in AAP-Medium at pH 6, 7, and 8 were estimated as 20.1, 5.4, and 150.6 µg/L, respectively, for dissolved Al.	The 96 h LC50 of aluminum to <i>Oncorhynchus mykiss</i> was 7.4 mg of Al/L at pH 6.5 and 14.6 mg of Al/L at pH 7.5	-	The 48-hr LC50 for <i>Ceriodaphnia dubia</i> exposed to Aluminium chloride increased from 0.72 to greater than 99.6 mg/L with water hardness increasing from 25 to 200 mg/L.
Tungsten	The 72 h EC50 of sodium	The 96 h LC50 of sodium	The 30 min EC50 of sodium	The 48 h EC50 of sodium

7440-33-7	tungstate to Pseudokirchnerella subcapitata was 31.0 mg of W/L.	tungstate to Danio rerio was greater than 106 mg of W/L.	tungstate for activated sludge were greater than 1000 mg/L.	tungstate to Daphnia magna was greater than 96 mg of W/L.
Tantalum 7440-25-7	-	-	-	-
Hafnium 7440-58-6	The 72 h EC50 of hafnium to Pseudokirchnerella subcapitata was greater than 8 ug of Hf/L (100% saturated solution).	The 96 h LC50 of Hafnium dioxide in water to Danio rerio was greater than the solubility limit of 0.007 mg Hf/L.	-	The 48 h EC50 of Hafnium dioxide to Daphnia magna was greater than the solubility limit of 0.007 mg Hf/L.
Vanadium 7440-62-2	The 72 h EC50 of vanadium pentoxide to Desmodesmus subspicatus was 2,907 ug of V/L.	The 96 h LC50 of vanadium pentoxide to Pimephales promelas was 1,850 ug of V/L.	The 3 h EC50 of sodium metavanadate for activated sludge was greater than 100 mg/L.	The 48 h EC50 of sodium vanadate to Daphnia magna was 2,661 ug of V/L.
Molybdenum 7439-98-7	The 72 h EC50 of sodium molybdate dihydrate to Pseudokirchnerella subcapitata was 362.9 mg of Mo/L.	The 96 h LC50 of sodium molybdate dihydrate to Pimephales promelas was 644.2 mg/L.	The 3 h EC50 of molybdenum trioxide for activated sludge was 820 mg/L.	The 48 h LC50 of sodium molybdate dihydrate to Ceriodaphnia dubia was 1,015 mg/L. The 48 h LC50 of sodium molybdate dihydrate to Daphnia magna was greater than 1,727.8 mg/L.
Zirconium 7440-67-7	The 14 d NOEC of zirconium dichloride oxide to Chlorella vulgaris was greater than 102.5 mg of Zr/L.	The 96 h LL50 of zirconium to Danio rerio was greater than 74.03 mg/L.	-	The 48 h EC50 of zirconium dioxide to Daphnia magna was greater than 74.03 mg of Zr/L.
Hydrogen 1333-74-0	-	-	-	-

Persistence and degradability**Bioaccumulation****Mobility****Other adverse effects****13. DISPOSAL CONSIDERATIONS****Waste treatment methods**

Disposal of wastes Disposal should be in accordance with applicable regional, national and local laws and regulations.

Contaminated packaging Disposal should be in accordance with applicable regional, national and local laws and regulations.

This product contains one or more substances that are listed with the State of California as a hazardous waste.

14. TRANSPORT INFORMATION

<u>DOT</u>	Regulated
UN/ID No.	3089
Proper shipping name	Metal powders, flammable, n.o.s. (Niobium Alloy Powder)
Hazard Class	4.1
Packing Group	II

Special Provisions IB8, IP2, IP4, T3, TP33
Emergency Response Guide Number 170

15. REGULATORY INFORMATION

International Inventories

TSCA	Complies
DSL/NDSL	Complies
EINECS/ELINCS	Complies
ENCS	Complies
IECSC	Complies
KECL	Complies
PICCS	Not Listed
AICS	Not Listed

Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory
DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List
EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances
ENCS - Japan Existing and New Chemical Substances
IECSC - China Inventory of Existing Chemical Substances
KECL - Korean Existing and Evaluated Chemical Substances
PICCS - Philippines Inventory of Chemicals and Chemical Substances
AICS - Australian Inventory of Chemical Substances

US Federal Regulations

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product does not contain any chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

SARA 311/312 Hazard Categories

Acute health hazard	No
Chronic Health Hazard	No
Fire hazard	Yes
Sudden release of pressure hazard	No
Reactive Hazard	No

CWA (Clean Water Act)

This product does not contain any substances regulated as pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

CERCLA

This material, as supplied, does not contain any substances regulated as hazardous substances under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302) or the Superfund Amendments and Reauthorization Act (SARA) (40 CFR 355). There may be specific reporting requirements at the local, regional, or state level pertaining to releases of this material

US State Regulations

California Proposition 65

This product does not contain any Proposition 65 chemicals

U.S. State Right-to-Know Regulations

Chemical Name	New Jersey	Massachusetts	Pennsylvania
Titanium 7440-32-6	X		

Aluminum 7429-90-5	X	X	X
Tungsten 7440-33-7	X	X	X
Tantalum 7440-25-7	X	X	X
Hafnium 7440-58-6	X	X	X
Vanadium 7440-62-2	X	X	X
Molybdenum 7439-98-7	X	X	X
Zirconium 7440-67-7	X	X	X
Hydrogen 1333-74-0	X	X	X

U.S. EPA Label Information

EPA Pesticide Registration Number Not applicable

16. OTHER INFORMATION

NFPA	Health hazards 0	Flammability 1	Instability 0	Physical and Chemical Properties -
HMIS	Health hazards 1	Flammability 2	Physical hazards 0	Personal protection X

Issue Date 12-Jan-2018

Revision Date 07-Sep-2021

Revision Note

SDS sections updated: 3

Note:

The information provided in this safety data sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet

Additional information available from: Safety data sheets and labels available at ATImetals.com